

1. 5Ah4S 电池组技术指标书

1.5Ah4S Battery pack indicator confirmation

序号 serial number	项目 Items	需求参数 Parameters	备注 Remark
1	标称容量 Nominal Capacity	1.5Ah	
2	标称电压 Nominal voltage	14.8V	
3	电量 Electric quantity	22.2Wh	
4	充电截止电压 Charging cut-off voltage	16.8V	
5	放电截止电压 Discharge cut-off voltage	12.8V	
6	标准充电电流 Standard charging current	0.75A	
7	最大充电电流 Maximum charging current	3A	
8	持续放电电流 Continuous discharge current	60A	持续 40C
9	最大脉冲放电电流 Maximum pulse discharge current	180A@3s	瞬时 120C
10	充电工作温度 Charge operating temperature	0~45°C	
11	放电工作温度 Discharge operating temperature	-20~60°C	
12	平衡线接口 Balanced line interface	JST XH2.54 5PIN 连接器	
13	充放电接口 Charge and discharge interface	XT60-12AWG 红黑特 软硅胶线	
14	保护板要求 BMS requirements	无	
15	外壳 Shell	PVC 膜热缩软包	
16	其他特殊要求 Other special requirements	无	
17	尺寸 (≤) Dimension	80×35×34±2mm	高*宽*厚
18	重量 (≤) Weight	0.18±0.01kg	

备注：以上技术指标对应本规格单个电池组，禁止擅自将本规格电池组再进行外部串并联使用。